SCOTSMAN

REMOTE COOLED MODULAR CONTOUR CUBERS



BIN OPTIONS:





SCOTSMAN MODULAR BINS

Model

Number

BH900

BH1100

BH1300

BH1600



BIN: BH1600

Application

Capacity

lbs./kg.

940/426

1100/499

1400/635

1755/796

Certified & rated in accordance with

ARI standard 820-95

Finish **

SS or BB

SS or BB

SS or BB

SS or BB

Ship

Weight

lbs./kg.

185/84

280/127

310/140

370/168

CME2006

VOLUME PRODUCTION • 24 HOUR

Certified & rated	Remote			
in accordance with ARI stan- dard 810-95	70°/50° lbs./kg.	ARI 90°/70° lbs./kg.		
сме2006-32	1930/874	1740/789		
сме2006-3	1930/874	1740/789		

VALUE THE DIFFERENCE OF CM3 ICE MACHINES:

- Featuring Food Service Industry's first scroll compressor by Copeland.
- CM³ series offers the lowest lifetime operating costs based on lower water and electrical usage. Combine that with a competitive purchase price and the best warranty in the industry and you have the lowest lifetime ownership cost. Period.
- AutoIQ™ Control System monitors and controls the ice machines' functions to ensure consistent ice production and reduce operating costs.
- CM³ Evaporator is a hot tin dipped, molecularly bonded plate that has been field tested and proven 99.4% reliable over 5 years.
- Rust-free Polyethylene Base & Food Zone is insulated with 1-1/2" of foam which keeps water and food zone cool to reduce operating costs and is backed by a Lifetime Rust-Free Warranty.
- Contemporary styling and stainless steel finish make the CM³ a perfect addition to any operation.
- Now protected with AquaArmor™ utilizing AgION™, a silver-based anti-microbial compound that reduces the growth of bacteria, microorganisms, algae, mold and slime on ice machine surfaces. AgION is a trademark of AgION Technologies and is registered with the EPA.

Agion

WARRANTY See your dealer for complete warranty details.

- · Limited Lifetime Rust Free Warranty on Food Zone.
- 3 years parts and labor on all components.
- 5 years parts and labor on the CME evaporator.
- 5 years parts on the compressor and condenser.



APPROX. CUBE SIZE: $1^{3}/8^{"} \times 1^{3}/8^{"} \times 5/8^{"}$ THICK









** SS - All Stainless Steel with Polyethylene Liner.

Dimensions

W"xD"xH" *

48.2 x 33.75 x 44

48 x 34 x 50

60 x 34 x 50

60 x 34 x 62

BB - All Stainless Steel Except Galvanized Back and Bottom

ARI Bin

Capacity

lbs./kg.

740/336


860/393


1100/499


1375/624





Ice Machine Specifications














All models: Dimensions: W x D x H Unit: 48" x 24" x 28" Shipping Carton: 51" x 27" x 31"												
	Model Number	Condenser Unit	Basic Electrical Volts/Hz/Phase	Max. Fuse Size or HACR Circuit Breaker	Comp. HP	Circuit Wires	Min. Circuit Ampacity	BTU's per hour	Shipping Weight lbs./kg.	Power Consumption KWH/100 lbs. 90°F/70° F	Water Gallons/ Potable 90°F/70° F	
	CME2006RS-32C	Rемоте	208-230/60/1	40	4.0	2	30	31,500	370/168	5.8	19.0	-
	CME2006RS-3C	Rемоте	208-230/60/3	30	4.0	3	20	31,500	370/168	5.8	19.0	-

All units with Stainless Steel finish.

Refrigerant: R-404A.
OPTIONS: Stacking Kit: KSCME6-LG-B

REMOTE CONDENSER—See ERC Spec Sheet for further details

Dimensions: W x D x H: 29.50" x 38.00" x 38.50"

Model			Finish	Electrical Volts/Hz/		Min. Circuit Ampacity	Max Fuse Size or HACR Circuit
Number	For Use With	Cond. Unit	Basic	Phase	No. of Wires	ranpacity	Braker
ERC611-32A	(1) CME2006R	Air	Galvanized	208-230/60/1	2	1.25	15

PRE-CHARGED REFRIGERANT TUBE KITS: 25-Foot, LRTE25-25 • 40-Foot, LRTE40-40 • 75-Foot, LRTE75-75, Refrigerant: R-404A.

Scotsman's ice machines are not designed for outdoor installations. Scotsman remote condensers are designed for outdoor installations.

Machine requires voltage indicated on rating name plate. Failures caused by improper voltage are not considered factory defects. Extended periods of operation at temperatures exceeding limitations constitutes misuse under the terms of Scotsman Manufacturer's Limited Warranty, resulting in a loss of warranty coverage. Specifications and design are subject to change without notice.

Consult Your Local SCOTSMAN Representative At:

IMPORTANT OPERATING REQUIREMENTS:

mir on the or end in the negotial mentals.							
	Minimum	Maximum					
Air Temperatures	50°F (10°C)	100°F (37.7°C)					
Water Temperatures	40°F (4.4°C)	100°F (37.7°C)					
Remote Cond. Temps	-20°F (-28.9°C)	120°F (48.9°C)					
Water Pressures	20 PSIG	120 PSIG					
Flectrical Voltage	-5%	+10%					

YOU'LL VALUE THE DIFFERENCE".